

DG-ST-X-LVB LED VANITY LIGHT

| | | | |
|------------------|--|--------------------|------------|
| Catalog # | | Prepared by | LiteHarbor |
| Project | | Date | |
| Notes | | | |



LED VANITY LIGHT

Description

This is a high lumen, thin, beautiful appearance, safe and reliable, convenient installation and easy maintenance led vanity light.

Customized residential and commercial lighting applications with this LED cylinder vanity light.

The contemporary cylinder is constructed of an acrylic diffuser with housing available in either a brushed nickel or chrome finish. The included canopy/junction box cover is removable for a more low profile look (2'-4' lengths only). The white acrylic diffuser provides even illumination and softens the appearance of the LEDs for improved aesthetics.)

Features

Using imported high transmittance PC cover, retain color for long time.

Available in 1x2, 1x3 and 1x4 models.

Beam Angle: 180 °.

Standard finish is powder coat textured white. Optional silver, black or custom color paint finishes.

Light Source

Using the energy-saving highlighting 2835 SMD LED light source.

Distributed LED array in a variety of lumen output packages.

LED color is available in 2700-6500K. Module is replaceable.

Standard dimming control: 0 ~ 10 v dimming.

Mounting

Wall mounted.



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Dec. 2017

Driver

Using isolation constant-current drive power, is the guarantee of security, stability and no flicking.

Listing&Warranty



Labels: ETL listed, conforms to UL Standard 1598 / 8750 and CSA Standard C22.2, damp location.

Warranty: 5-year limited warranty on LED and Driver.

Specification

| | |
|---------------|----------------|
| Power | 20W/30W/40W |
| Voltage | 120V ~ 277V AC |
| Frequency | 50/60Hz |
| Power factor | >0.98 |
| CRI | 80+/90+ |
| Dimmable | NONE/0-10V |
| CCT | 2700-6500K |
| Lifespan | 50000 H |
| Certification | ETL listed |

Dimension



Packing

2ft: 610*123*93mm

Inner box: 615*130*100mm 1 pcs/Box Outer box: 63*42*15.5CM 4PCS/CTN

3ft: 915*123*93mm

Inner box: 920*130*100mm 1 pcs/Box Outer box: 93.5*42*15.5CM 4PCS/CTN

4ft: 1219*123*93mm

Inner box: 1225*130*100mm 1 pcs/Box Outer box: 124*42*15.5CM 4PCS/CTN



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Dec. 2017

Ordering Guide

| Series | Length | Watt | Lumen | Mounting |
|--------------------------------------|-------------------------------|------------------------------|---------------------------------|---------------------------------------|
| <input type="checkbox"/> DG-ST-2-LVB | <input type="checkbox"/> 2 Ft | <input type="checkbox"/> 20W | <input type="checkbox"/> 1600lm | <input type="checkbox"/> Wall Mounted |
| <input type="checkbox"/> DG-ST-3-LVB | <input type="checkbox"/> 3 Ft | <input type="checkbox"/> 30W | <input type="checkbox"/> 2500lm | |
| <input type="checkbox"/> DG-ST-4-LVB | <input type="checkbox"/> 4 Ft | <input type="checkbox"/> 40W | <input type="checkbox"/> 3400lm | |

LED Vanity Light

| Dimming | Finish |
|--|---------------------------------|
| <input type="checkbox"/> NONE | <input type="checkbox"/> White |
| <input type="checkbox"/> 0-10V Dimming | <input type="checkbox"/> Silver |
| | <input type="checkbox"/> Black |



Notes:

1. To ensure normal working of the product, please make sure that the voltage using is within the indicated voltage range.
2. Please follow the correct method to install and use this product.
3. Disconnect the power supply when installing and removing the product to avoid the risk of electric shock.
4. Do not look at the LED light source for a long time; high-intensity light source may cause eye damage.
5. When you find the following questions, please consult with a qualified electrician for repair service.

Do not disassemble yourself:

- A. When the product produces stench gas, abnormal sound, or unusual flicker.
 - B. When the shell is damaged, the foreign body intrudes inside.
6. The parameters in this specification may be modifying according to product update.



Liteharbor Lighting Technology Co., Ltd.

New Industry Area Hecun Danzao Town
Nanhai Foshan City Guangdong China

TEL: +86-757-8180 8675

FAX: +86-757-8180 8685

E-mail: info@liteharbor.com

Website: www.liteharbor.com

Specifications subject to change w/o notice

Revision: Dec. 2017